



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY  
WASHINGTON, DC 20460

OFFICE OF CHEMICAL SAFETY  
AND POLLUTION PREVENTION

July 9, 2018

Brigette Bartko  
Product Stewardship Manager, US & Canada  
PPG Architectural Finishes, Inc.  
PPG Industries, Inc.  
One PPG Place  
Pittsburgh, PA 15272

Subject: Notification per PRN 98-10 – Minor Label Change  
Product Name: ABC 3 Marine Antifouling Paint  
EPA Registration Number: 7313-18  
Application Date: June 25, 2018  
Decision Number: 542506

Dear Ms. Bartko:

The Agency is in receipt of your Application for Pesticide Notification under Pesticide Registration Notice (PRN) 98-10 for the above referenced product. The Antimicrobials Division (AD) has conducted a review of this request for its applicability under PRN 98-10 and finds that the action requested falls within the scope of PRN 98-10.

The label submitted with the application has been stamped “Notification” and will be placed in our records.

Should you wish to add/retain a reference to the company’s website on your label, then please be aware that the website becomes labeling under the Federal Insecticide Fungicide and Rodenticide Act and is subject to review by the Agency. If the website is false or misleading, the product would be misbranded and unlawful to sell or distribute under FIFRA section 12(a)(1)(E). 40 CFR 156.10(a)(5) list examples of statements EPA may consider false or misleading. In addition, regardless of whether a website is referenced on your product’s label, claims made on the website may not substantially differ from those claims approved through the registration process. Therefore, should the Agency find or if it is brought to our attention that a website contains false or misleading statements or claims substantially differing from the EPA approved registration, the website will be referred to the EPA’s Office of Enforcement and Compliance.

If you have any questions, you may contact Joe Daniels at (703) 347-8669 or via email at [daniels.joseph@epa.gov](mailto:daniels.joseph@epa.gov).

Sincerely,

A handwritten signature in blue ink that reads "E. Miederhoff". The signature is written in a cursive style with a large, stylized initial "E".

Eric Miederhoff  
Product Manager 31  
Regulatory Management Branch I  
Antimicrobials Division (7510P)  
Office of Pesticide Programs

**[EPA MASTER LABEL COPY]**

**ABC® 3 Marine Antifouling Paint**

**[Alternate brand names:]**

**ABC® 3 Marine Antifouling Paint**  
**[Alternate color descriptors:]**  
**BLACK – ABC3-92**  
**RED – ABC3-72**  
**LIGHT BLUE – ABC3-41**  
**Type 223 Black – AT223-9**

**Amercoat 214**  
**[Alternate color descriptors:]**  
**BLACK – AT214-91**

**NOTIFICATION**

7313-18

The applicant has certified that no changes, other than those reported to the Agency have been made to the labeling. The Agency acknowledges this notification by letter dated:

07/09/2018

**[FOR USE IN COMMERCIAL SHIPYARDS ONLY]**  
**[Only for use on commercial vessels]**  
**[Only for use on commercial vessels in California]**  
**[Not for recreational vessels]**  
**[Not for recreational vessels in California]**

**EPA Reg. No. 7313-18**  
**EPA Est. No. 7313-AR-1**

**ACTIVE INGREDIENT: Cuprous Oxide . . . 47.99%**  
**OTHER INGREDIENTS: . . . . . 52.01%**  
Copper as metallic: 42.3%  
Contains Petroleum Distillates

**KEEP OUT OF REACH OF CHILDREN**  
**WARNING**

See other precautions on side panel and MSDS.

**Manufactured by**  
**PPG Industries, Inc.**  
**PPG Architectural Finishes, Inc.**  
**One PPG Place**  
**Pittsburgh, PA 15272**  
**Emergency Telephone Number: 1-412-434-4515**  
**Manufactured in the U.S.A.**

**[Alternate container weights :]**  
**NET CONTENTS 1 US gallons (3.79 liters)**  
**NET CONTENTS 5 US gallons (18.93 liters)**  
**NET CONTENTS 35 US gallons (132.49 liters)**

**NOTE:** This product contains a chemical(s) known to the state of California to cause cancer.

Photochemically Reactive per SCAQMD Rule 102  
Shelf life: 1 year from date of shipment  
DOT: Paint, UN1263  
VOC: 400 g/L, 3.2 lbs/gal  
Thinned: T-10 (1 pt/gal) 433 g/L, 3.6 lbs/gal  
Do not thin inconsistent with local VOC regulations.

***[06/25/2018 pending EPA update, approved xxxxxx]***

## **PRECAUTIONARY STATEMENTS**

### **HAZARDS TO HUMANS AND DOMESTIC ANIMALS:**

**WARNING** – Causes severe eye irritation. May cause moderate skin irritation. May be harmful if absorbed through the skin. Prolonged or repeated contact may cause an allergic skin reaction. Vapor irritates eyes, nose, and throat. Vapor and/or spray mist may be harmful if inhaled. May cause irritation and/or allergic respiratory reaction in lungs. Harmful or fatal if swallowed.

### **FIRST AID:**

**Have the product container or label with you when calling a poison control center or doctor, or going for treatment.**

**If in eyes:** Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for treatment advice.

**If on skin or clothing:** Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment advice.

**If swallowed:** Call poison control center or doctor immediately for treatment advice. Have person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by a poison control center or doctor. Do not give anything by mouth to an unconscious person.

**If inhaled:** Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth to mouth, if possible. Call a poison control center or doctor for treatment advice.

**For emergency medical information, call 1-412-434-4515.**

**Hygienic practices** – Wash thoroughly after use and before eating, smoking or using washroom. Keep away from feed or food products. Launder contaminated clothing before use.

**ENVIRONMENTAL HAZARDS:** This product is toxic to fish. Do not apply directly to water by cleaning, equipment or disposal of wastes or allow chips and dust generated during paint removal to enter water.

**PHYSICAL OR CHEMICAL HAZARDS:** Flammable. Keep away from heat, sparks, arc and open flame. Avoid breathing vapor, dust, spray mist or contact with eyes and skin. Use only with adequate ventilation and wear protective equipment, such as goggles, face protection, gloves, full protective clothing and properly fitted, positive-pressure, air-supplied respirator, during mixing, spraying and drying, until all vapors and mists are gone. There are reports that associate repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. In confined, poorly ventilated areas, use airline, hood-type respirator and explosion- and spark-proof equipment. Welding and cutting can produce hazardous fumes and gases. **For fires**, blanket flames with foam, carbon dioxide, dry chemical. **For spills**, eliminate all sources of ignition or sparks. Use absorbent cleanup materials; place in separate, closed, metal container and dispose of in accordance with all applicable regulations. Wear NIOSH certified, self-contained air-supplied respirators to prevent overexposure to vapors.

**DIRECTIONS FOR USE:** It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

**Surface Preparation** – Dependent upon the condition of the hull and existing antifouling coatings, surface preparation will vary from low pressure water cleaning (1500-3000 psi) to abrasive blasting. Apply over a suitable primer system or clean, intact, existing antifouling coating. Substrates that are abrasive blasted should be prepared in accordance with the instructions for the anticorrosive coating to be used.

**Application Equipment** – Can be applied by brush, roller, airless spray, or conventional air spray equipment.

**Application Instructions** –

1. When applying antifouling coatings over epoxy anticorrosive coatings, apply the first coat of antifouling while the epoxy anticorrosive is tack free, but still soft to thumb pressure. If the epoxy is too hard, apply another thin coat of epoxy and then apply the antifouling after the epoxy is tack free but still soft to thumb pressure. Failure to apply the antifouling coating while the epoxy is thumbprint soft may result in poor adhesion of the antifouling coating and eventual delamination.
2. Clean all application equipment with T-10 thinner.
3. Stir material thoroughly and continue stirring occasionally during application to ensure pigment suspension.
4. Thin only for workability – no more than 1 pint thinner per gallon of material.
5. Apply a wet coat in even brush or roller strokes or spray passes, building the wet film thickness to achieve the recommended dry film thickness. Allow 4 hours dry time at 77°F (20°C) between coats. Allow 5 hours dry time at 77°F (20°C) before launching.
6. Clean application equipment immediately after use with thinner.

**STORAGE AND DISPOSAL:** Keep container closed when not in use. Store in cool, dry, well-ventilated area. Do not contaminate water, food or feed by storage or disposal. **Pesticide Disposal:** Pesticide wastes are toxic. Improper disposal of this product or its rinsate is a violation of Federal Law. If this product cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or Regional EPA Office, Hazardous Waste. **Container Disposal:** Nonrefillable container. Do not reuse or refill this container. Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

**LIMITED WARRANTY** – PPG warrants your satisfaction with the performance properties of this product if it is properly applied to a properly prepared surface in accordance with label directions. PPG MAKES NO OTHER EXPRESS WARRANTIES. IN THE EVENT THE PRODUCT FAILS TO CONFORM TO THIS WARRANTY, PPG AS ITS SOLE LIABILITY AND IN LIEU OF ANY DIRECT OR INDIRECT, INCIDENTAL, SPECIAL OR CONSEQUENTIAL DAMAGES, WILL, AT YOUR OPTION, FURNISH REPLACEMENT PRODUCT OR REFUND THE PURCHASE PRICE - LABOR OR COSTS OF LABOR FOR THE APPLICATION OF ANY PRODUCT SPECIFICALLY ARE EXCLUDED. You must supply proof of purchase. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. To make a claim under this warranty contact the store where you purchased the product or; PPG Industries, Inc., One PPG Place, Pittsburgh, PA 15272.